


\*) Place the Manufacturer-ID and the UL-Number in the Solder Stop Bottom  
Base material of P.C.B. according to UL94 V0

Mat.: FR 4		Cu 35/35	chem. Ni/Au	Drill-Diameter in mm (Final hole diameter)	
Soldermask: white		Silkscreen: black		Tolerance Drill-Diameter: IPC-A-600 Klasse II	
-	-	-	-	NEMONOS	
-	-	-	-		
-	-	-	-	Embedded System Design	
-	-	-	-		
-	-	-	-	Production Drawing	
-	-	-	-		
-	-	-	-	Scale	
-	-	-	-		
-	-	-	-	Dok.-Nr.:	
-	-	-	-		
-	-	-	-	TMC2160-EVAL V1.0	
-	-	-	-		
1.0	New	04.06.11	WW	TRINAMIC	
Rev.	Modificat.	Date	Name		

Top Side	
Solder Mask	
Cu	35µm
Prepreg. 180µm	
Cu	180µm
FR4, 710µm	
Cu	35µm
Prepreg. 180µm	
Cu	180µm
Prepreg. 180µm	
Cu	35µm
Solder Mask	
Bottom Side	
Solder Mask	
Cu	35µm
Prepreg. 180µm	
Cu	180µm
FR4, 710µm	
Cu	35µm
Prepreg. 180µm	
Cu	180µm
Prepreg. 180µm	
Cu	35µm
Solder Mask	



SIZE	QTY	SYM	PLATED	TOL
0.3	488	+	YES	+/-0.1
1	12	x	YES	+/-0.1
1.3	4	□	YES	+/-0.1
1.5	2	◇	YES	+/-0.1
3.2	4	⊗	YES	+/-0.1
1.1	44	⊞	NO	+/-0.1
1.8	2	⊕	NO	+/-0.1

TMC2160-EVAL V1.0 04.06.2018